



US006340320B1

(12) **United States Patent**
Ogawa

(10) **Patent No.:** **US 6,340,320 B1**
(45) **Date of Patent:** **Jan. 22, 2002**

(54) **PROBE PIN ASSEMBLY, A METHOD OF MAKING THE SAME AND A CONNECTOR USING THE SAME**

(75) Inventor: **Shingo Ogawa**, Tokyo (JP)

(73) Assignee: **Honda Tsushin Kogyo Co., Ltd.**,
Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/266,612**

(22) Filed: **Mar. 11, 1999**

(30) **Foreign Application Priority Data**

Dec. 18, 1998 (JP) 10-360557

(51) **Int. Cl.⁷** **H01R 13/24**

(52) **U.S. Cl.** **439/824; 439/700; 29/511**

(58) **Field of Search** 439/824, 700,
439/886; 29/511

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,438,350 A * 3/1948 Reichard 439/219

4,580,856 A * 4/1986 Westover et al. 439/34
4,603,329 A * 7/1986 Bangerter et al. 340/679
4,614,388 A * 9/1986 Powell 439/82
4,669,185 A * 6/1987 Westover et al. 29/82
5,044,993 A * 9/1991 El-Haj et al. 439/668
5,461,326 A * 10/1995 Woith et al. 439/482
5,482,038 A * 1/1996 Ruff 439/482

* cited by examiner

Primary Examiner—Renee Luebke

Assistant Examiner—Brigitte R. Hammond

(74) *Attorney, Agent, or Firm*—Arent Fox Kintner Plotkin
& Kahn, PLLC

(57) **ABSTRACT**

Disclosed are an improved probe pin assembly and a method of making the same. Each probe pin uses a sleeve which is formed by stamping and deep-drawing a thin sheet of metal with dies. The sleeve has a contact pin slidably fitted therein, a resilient member contained therein to spring-bias the contact pin with its tip end appearing from the sleeve and a cover plate fastened to and closing the rear opening of the sleeve.

2 Claims, 4 Drawing Sheets

